



"RUPI CABLE- AND WIRE STOCKINGS,  
SIMPLY BRILLIANT AND INDISPENSABLE"

# RUPI-COLOGNE<sup>®</sup>, INC.

**YOUR SPECIALIST AROUND CABLE AND WIRE**

## Cable and rope joining stockings

### >> RP- 600-G



Mainly for fastening, holding and mounting as well as the strain relief of movable cables and lines on cranes, shaft and lifting devices. The advantage against conventional suspensions with clamps lies in the prevention of point stress and excluding kinking and breaking leads.

These stockings are particularly suitable and in use worldwide for wind power plants, suspension railways and cranes. The highly flexible mesh made of double galvanized steel strands is hand-woven and fitted with a suspension eyelet (round thimble).



(2-layered / standard)



(3-layered / enhanced)

**RP-600-G:** Available in standard lengths 700 mm (500 mm braiding 200 mm head). Other lengths upon request!  
Also available in the following design:

>> **STAINLESS STEEL (STAINLESS STEEL BRAIDING)**

>> **STRAINED BOWDEN CABLE**

>> **STAINLESS STEEL REINFORCED** (three-layer design for higher tensile strength)

>> **PLASTIC COATED STRANDS**



**rupi-Cologne, Inc.**

2100 Skyline View Lane  
NIXA, MO 65714  
U.S.A.

**Phone + Fax**

1-417-883-9939  
1-417-883-9949

**E-mail + Web**

info@rupi-cologne-inc.com  
www.rupi-cologne-inc.com



"RUPI CABLE- AND WIRE STOCKINGS,  
SIMPLY BRILLIANT AND INDISPENSABLE"

**RUPI-COLOGNE<sup>®</sup>, INC.**

**YOUR SPECIALIST AROUND CABLE AND WIRE**

## Cable and rope support stockings

### >> RP- 600-G

| For cables and ropes<br>with $\varnothing$ from - to | Permissible tension load<br>in kN / tons<br>approx. | Thimble size<br>for bolt $\varnothing$<br>approx. mm | Part number  |
|--|---|--|--------------|
| 08 - 15 mm   | 5,12 / 0,52   | flexible rope eyelets                                | RP - 610 - G |
| 15 - 20 mm   | 6,40 / 0,65   | flexible rope eyelets                                | RP - 615 - G |
| 20 - 30 mm   | 6,40 / 0,65   | flexible rope eyelets                                | RP - 620 - G |
| 30 - 40 mm   | 8,96 / 0,91   | flexible rope eyelets                                | RP - 630 - G |
| 40 - 50 mm   | 12,48 / 1,27  | flexible rope eyelets                                | RP - 640 - G |
| 50 - 60 mm   | 13,87 / 1,41  | flexible rope eyelets                                | RP - 650 - G |
| 60 - 80 mm   | 13,87 / 1,41  | flexible rope eyelets                                | RP - 660 - G |
| 70 - 80 mm   | 25,60 / 2,61  | flexible rope eyelets                                | RP - 670 - G |
| 80 - 100 mm  | 28,80 / 2,94  | flexible rope eyelets                                | RP - 680 - G |
| 100 - 120 mm   | 35,60 / 3,63  | flexible rope eyelets                                | RP - 6100- G |



**Greater loads and higher tensile forces  
and special designs on request.  
Produceable immediately.**

#### rupi-Cologne, Inc.

2100 Skyline View Lane  
NIXA, MO 65714  
U.S.A.

#### Phone + Fax

1-417-883-9939  
1-417-883-9949

#### E-mail + Web

info@rupi-cologne-inc.com  
www.rupi-cologne-inc.com